

Microplate Reader

PKL PPC 142 Microplate Reader

- It is controlled by computer to complete Enzyme Linked
- Immunosorbent Assay (ELISA). Read 48 well and 96 well microplate, analyse and report, which are widely used in clinical diagnostic laboratories, centers for disease control and prevention, animal and plant quarantine, animal husbandry and veterinary epidemic prevention stations, biotechnological industries, food industries, environmental science, agricultural scientific research and other academic organizations.



Features

- Built-in computer, 8" touch screen, edit, test, save, print efficiently and conveniently.
- 8 channels zero dispersion monochromatic optical fiber testing system, automatic well center positioning.
- High-precision rail transmissions, enclosing optical system, test 96 wells in 3 seconds.
- System self-check and diagnosis function for optical paths and mechanical parts.
- Lamp's automatic switch, energy-efficient design can extend the life of light source and make easy to change lamp.
- Shaking function, adjustable shaking speed and time.
- New Windows graphical user interface, operation system in English.
- Specimen information records: lists and cards, directly input specimen No., Patient Name, etc.

ISO9001:2015 ISO13485:2016



- Specimen No., OD value, result, S/CO value and item parameters can be shown in the same screen.
- Quick tagging blank, specimen, positive control, quality control, multi-valued comparison.
- Arrange 96 well microplate horizontally or longitudinally, set up optionally the start bit and stop bit in testing, autocoding.
- Suitable for self contrast, rows and columns subtraction, input judgment formula freely.
- Qualitative and quantitative parameters, the storable standard curve can be used directly.
- Multi-item can be tested on one microplate, up to 12 items.
- Report according to microplate No. or specimen No., input experimental items and results in batches.
- Inquiry and statistic analysis can be done according to the specimen No. and name, automatically track and analyse changing trends in data.
- Test data can be saved in MS Excel for further analysis.

Specifications:

- Light Source: 6V, 10W tungsten halogen lamp, it can work over 5000 hours
- Wavelength Range: 400-750 nm
- Optical Filters: 4 standard filters: 405, 450, 492, 630 nm, maximum 8 filters
- Measurement Methods: single wavelength, dual wavelength, two points method, dynamic assay, multiple wavelengths
- Blank Ways: single well blank, multiple wells blank, rows and columns blank
- Calculation Method: Linear, Conic, Semi-log, In, Log-Log, Point-Point, Four_Parametric, Spline
- Measurement Speed: single wavelength < 3 seconds/96 wells, dual wavelength < 9 seconds/96 wells
- Measurement Range: 0.0000-4.5000Abs
- Resolution: 0.0001A
- Linearity: $\pm 0.5\%$ or $< 0.025 A$
- Repeatability Difference: $< 0.1\%$ or $\pm 0.0025A$
- Rows and Columns Difference: $< 0.01 A$
- Display: built-in XP system, 8" touch-screen, shows whole microplate results and calibration curve
- Save Information: more than 300 test programs, results of 50 pieces of 96 well, 100000 test results
- Interface: 2 USB two-way communication interface, 1 RS232, 1 VGA, 1 LAN
- Environment: power supply: 12V DC (1 OOV-240V wide input voltage range); temperature: 5'C-40'C; humidity:
 - 10%-90%
- External Dimension: 52.5cm(20.7 in) x 42.0cm(16.5 in) x 26.0cm(10.20 in)
- Net Weight: 9kg

ISO9001:2015 ISO13485:2016

